

CraneKit with single girder trolley NOVA L without hoist

Technical Details:

FEM class	2M FEM	
Safe Working Load	5000 KG	
Power voltage	400 V	
Control voltage	48 V	
Frequency	50 HZ	
Lifting height	6 M	
Hoisting speed (high)	5 MMIN	
Hoisting speed (low)	0.83 MMIN	
Trolley speed (high)	20 MMIN	
Trolley speed (low)	5 MMIN	
Falls	04	1x4-falls, normal reeving
Trolley type	L	Double girder, medium connect
Flange width/B-measure	400 MM	
Type of hoist control	2SP	Two speed
Hoist motor type	P	Pole change motor
Hoist motor size	3	4.5. kW (50 Hz)
Type of travel control	DYD	DMCS inverter control
Trolley travel inverter power rating	007F	007F
Trolley travel inverter resistor type	N	Standard (DYD)
Trolley travel control method	MS2	Two step with ramps
Trolley acceleration time	3.4 S	3.5 seconds
Travel motor type	T	Frequency converter motor
Overload device type	MEC	Mechanical limit switch
Condition monitoring type	NO	No condition monitoring unit
Electric provisions	CRANE	Hoist for crane
Electric norm	IEC	Standard IEC assembly
1-step limit switch, trolley motion:	Slow down	
Language of the plates	EN	English
Crane Span:	20 M, Left	
Runway Length:	35 M	
Endtrucks:	ET14-2765-P60000A0000-N	
Travel motors:	GES342PS3BOF06LA200-5400N, Bridgespeed high/slow:25/6.2 m	
Crane cubicle:	SWFNELP3-1QQ400-20H0	
Power supply hoist:	QQEHS12L9CP320200	
Power supply crane:	RC4-4XCU50-35M	
Pendant:	PBS082221D00-N060PE10	
Radio remote control:	RM2SS1100TDRPCE	

Please contact:

Verena Eder

Sales Assistant

Office Manager Sales

Phone: +49(0)621.78990-215

Fax: +49(0)621.78990-120

Email: verena.eder[at]swfkrantechnik.com