

## 1 x Low headroom wire rope hoist NOVA Blackline L crane kit

### Type Code BB04L5AFP130AP1F

#### Technical Details:

FEM class	2M FEM	
Safe Working Load	1.000 KG	
Power voltage	400 V	
Control voltage	48 V	
Frequency	50 HZ	
Lifting height	6 M	
Hoisting speed (high)	5.00 MMIN	
Hoisting speed (low)	0.83 MMIN	
Trolley speed (high)	20.0 MMIN	
Trolley speed (low)	5.0 MMIN	
Falls	04	1x4-falls, normal reeving
Trolley type	L	Low Headroom
Hoist motor type	P	Pole change motor
Hoist motor size	1	1,8 kW high, 0,25 kW low (50 Hz)
Trolley travel control method	2-speed	
Overload device type	MEC	Strain Gauge
Condition monitoring type	NO	
Electric provisions	CRANE	Hoist for crane
Electric norm	IEC	Standard IEC assembly
Language of the plates	GE	German
Crane Span:	4,5 M	
Endtrucks:	ETL09-2060-A30000A0000-N	
Travel motors:	GES320PS4BOF06MA200-5400E	
Bridgespeed high/slow:	32 / 8 m/min	
Crane cubicle:	SWFNELP1-12M400-20H0	
Power supply hoist:	QQEHS11L3BP120045-	
Radio :	TRR1525T192500TDRX0	
Documents:	included	

Please contact:

#### Robert Menstell

Sales Director Germany

Phone: +49(0)173 3489892

E-Mail: [robert.menstell@swfkrantechnik.com](mailto:robert.menstell@swfkrantechnik.com)